

コード構成（内容は仕様書で確認してください。）

⑥本体材質 / ⑦ボール材質 / ⑧シート材質 / ⑨呼び径 / ⑩オプション

制御	タイプ	①操作機型式		③電源電圧	⑨呼び径 (A)	V015		V020		V025		V032	
					④ランク	0	2	0	2	0	2	0	2
比例制御	コンパクト	PAX	4~20mA、1~5V	1	AC100/110V	050	120		120				
				2	AC200/220V								
	エコノミー	AEX	4~20mA・1~5V 抵抗入力、他	1	AC100/110V	120		120	360	120	360	120	360
				2	AC200/220V								
		PEX	高速作動 4~20mA・1~5V	6	AC100~240V	120		120	300	120	300		
				0	DC24V								
	スタンダード	PDX	4~20mA・1~5V 抵抗入力、他	1	AC100/110V	300		300		300		300	
				2	AC200/220V								
				3	AC24V								
				0	DC24V								
				7	AC115/120V								
				8	AC230/240V								
	ハイパフォーマンス	PHX	高頻度用 4~20mA・1~5V	1	AC100/110V	300		300		300		300	
				2	AC200/220V								
				3	AC24V								
				0	DC24V								
				7	AC115/120V								
				8	AC230/240V								
無線リモコン	コンパクト	RAM	リモコン操作	1	AC100/110V	070		070					
				2	AC200/220V								
	スタンダード	RAD	リモコン操作・振替入力	1	AC100/110V	300		300		300			
				2	AC200/220V								
		RHD	高速作動 リモコン操作・振替入力	0	DC24V	300		300		300			
				1	AC100/110V								
緊急遮断	ハイパフォーマンス	PBX	比例制御用 4~20mA・1~5V 電源喪失で緊急作動	2	AC200/220V	300		300		300			
				3	AC24V								
				0	DC24V								
				1	AC100/110V								