

型式: □□□ **HH** □ □ **5 S U** □ - □□□ - □□

コード構成 (内容は仕様書で確認ください。)

- ①操作機型式 / ②バルブ型式 / ③電源電圧 / ④ランク / ⑤接続規格
 ⑥本体材質 / ⑦ボール材質 / ⑧シート材質 / ⑨呼び径 / ⑩オプション

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

制御	タイプ	①操作機型式		③電源電圧		⑨呼び径 (A)	010		015	020	025	
						④ランク	1	0	0	0	0	
ON-OFF	スタンダード	AD1	電源振替入力	1	AC100/110V		300	700				
				2	AC200/220V							
		AD2	a接点信号入力	1	AC100/110V		300	700				
				2	AC200/220V							
				0	DC24V							
				7	AC115/120V							
				8	AC230/240V							
		AD0	極性反転入力	0	DC24V		300	700				
		HD1	高速作動 電源振替入力	1	AC100/110V		300	700			02K	
				2	AC200/220V							
		HD2	高速作動 a接点信号入力	1	AC100/110V		300	700			02K	
				2	AC200/220V							
0	DC24V											
HDO	高速作動 極性反転入力	0	DC24V		300	700			02K			
無線リモコン	スタンダード	RAD	リモコン操作・振替入力	1	AC100/110V		300	700				
				2	AC200/220V							
				0	DC24V							
		RHD	高速作動 リモコン操作・振替入力	1	AC100/110V		300	700			02K	
				2	AC200/220V							
				0	DC24V							