

型式： □□□ L2 □ □ 1 □ □ □ □ - □□□ - □□

コード構成 (内容は仕様書で確認してください。)

①操作機型式 / ②バルブ型式 / ③電源電圧 / ④ランク / ⑤接続規格
⑥本体材質 / ⑦ボール材質 / ⑧シート材質 / ⑨呼び径 / ⑩オプション

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

制御	タイプ	①操作機型式		③電源電圧	⑨呼び径 (A)	020	025		040		050		065		080	100	
					④ランク	0	0	2	0	2	0	2	0	2	0	0	
ON-OFF	エコノミー	AE1	電源振替入力	1	AC100/110V	120	360			360	700		02K				
				2	AC200/220V												
		AE2	a接点信号入力	1	AC100/110V	120	360			360	700		02K				
				2	AC200/220V												
	0			DC24V	120	360			360								
	スタンダード	AD1	電源振替入力	1	AC100/110V	300			300	700		700					
				2	AC200/220V												
		AD2	a接点信号入力	1	AC100/110V	300			300	700		700					
				2	AC200/220V												
				0	DC24V												
				7	AC115/120V												
		8	AC230/240V														
		AD0	極性反転入力	0	DC24V	300			300	700		700					
		HD1	高速作動 電源振替入力	1	AC100/110V	300			300	700		700		02K			
				2	AC200/220V												
		HD2	高速作動 a接点信号入力	1	AC100/110V	300			300	700		700		02K			
2				AC200/220V													
0	DC24V																
HD0	極性反転入力	0	DC24V	300			300	700		700		02K					
ハイパフォーマンス	PHR	高頻度用 a接点信号・振替入力	1	AC100/110V	300	700		300	700		700		02K				
			2	AC200/220V													
			3	AC24V													
			0	DC24V													
制御	タイプ	①操作機型式		③電源電圧	⑨呼び径 (A)	020	025		040		050		065		080	100	
					④ランク	0	0	2	0	2	0	2	0	2	0	0	
比例制御	エコノミー	AEX	4~20mA・1~5V 抵抗入力、他	1	AC100/110V	120	360				700		02K				
				2	AC200/220V												
	スタンダード	PDX	4~20mA・1~5V 抵抗入力、他	1	AC100/110V	300	700	300	700		700		02K				
				2	AC200/220V												
				3	AC24V												
				0	DC24V												
				7	AC115/120V												
	8	AC230/240V															
	ハイパフォーマンス	PHX	高頻度用 4~20mA・1~5V	1	AC100/110V	300	700	300	700		700		02K				
				2	AC200/220V												
				3	AC24V												
				0	DC24V												
7				AC115/120V													
8	AC230/240V																
無線リモコン	スタンダード	RAD	リモコン操作・振替入力	1	AC100/110V	300			300	700		700					
				2	AC200/220V												
				0	DC24V												
		RHD	高速作動 リモコン操作・振替入力	1	AC100/110V	300			300	700		700		02K			
				2	AC200/220V												
				0	DC24V												