

型式: □□□ **PL** □ □ □ □ □ □ □ - □□□ - □□

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

コード構成 (内容は仕様書で確認してください。)

①操作機型式 / ②バルブ型式 / ③電源電圧 / ④ランク / ⑤接続規格

⑥本体材質 / ⑦ボール材質 / ⑧ステムシール材質 / ⑨呼び径 / ⑩オプション

制御	タイプ	①操作機型式		③電源電圧		⑨呼び径 (A)	015	020	025	032	040	050	065	080	100													
						④ランク	0	0	0	0	0	0	0	0	0	2												
ON-OFF	ミニ	CM1	電源振替入力	1	AC100/110V	070																						
				2	AC200/220V																							
		CM2	a接点信号入力	1	AC100/110V												070											
				2	AC200/220V																							
	コンパクト	AM1	電源振替入力	1	AC100/110V	070	180																					
				2	AC200/220V																							
		AM2	a接点信号入力	1	AC100/110V	070	180																					
				2	AC200/220V																							
		AH1	高速作動 電源振替入力	1	AC100/110V	070	180																					
				2	AC200/220V																							
	エコミー	AE1	電源振替入力	1	AC100/110V	120	300	600	02K																			
				2	AC200/220V																							
AE2		a接点信号入力	1	AC100/110V	120	300	600	02K																				
			2	AC200/220V																								
無線リモコン	コンパクト	RAM	リモコン操作	1	AC100/110V	070																						
				2	AC200/220V																							