



Size [mm]	d	L	D	C	n-h	H	Weight [kg]	Cv	Actuator	Sizing code
40	40	40	80	95	4-15	384	11	85	PBX-300	0
50	50	40	90	105	4-15	389	11	145	PBX-300	0
65	65	40	115	130	4-15	401	12	290	PBX-300	0
80	80	50	126	145	4-19	433	13	450	PBX-300	0
100	105	50	146	165	8-19	444	13	780	PBX-300	0
125	130	50	181	200	8-19	461	14	1200	PBX-300	0
150	154	50	211	230	8-19	476	15	1800	PBX-300	0
200	204	50	257	280	8-23	499	17	3200	PBX-300	0
250	253	50	322	345	12-23	521	20	5100	PBX-300	0
							20		PBX-700	2
300	300	55	367	390	12-23	547	24	7200	PBX-300	0
							24		PBX-700	2
350	340	70	410	435	12-25	598	8900	PBX-700	0	
						620		PBX-02K	2	
400	387	70	470	495	16-25	622	11000	PBX-700	0	
						644		PBX-02K	2	

NOTE
ATTACHMENT
Cable gland (nylon), G 1/2, for 6φ to 12φ cable.
Plug.

No	DESCRIPTION	MATERIALS	REQ'D	REMARKS
7	Actuator	AC4C	1	
6	Joint	SCS13A	1	
5	Bracket	SUS304	1	
4	Gland Packing	GRAPHITE	1	
3	Stem	SUS420J2	1	
2	Disk	SUS420J2/J1	1	
1	Body	SCS13A	1	

MARK	DATE	BY	DATE	APPR'D	H.F	TITLE	J5K Flanged-end (Wafer type) WT type electric actuated control damper				
				CHK'D	K.Y	MODEL	PBXWT**2TG0				
				DESIGN		SCALE	NON	DWG No.	WT-*2TG0-BX2-EN		
				DRAWN	S.O						
REVISIONS											
MV-2691											