

Product code    **BR**        -

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

Code configuration (The contents are described in the specifications.)  
 ①Actuator model / ②Valve model / ③Voltage / ④Sizing / ⑤Connection  
 ⑥Body material / ⑦Ball material / ⑧Seat material / ⑨Size / ⑩Option

Type	Category	①Actuator model		③Voltage	⑨Size(A)	015	020	025	032	040	050	065	080	100	125	150		
					④Sizing	0	0	0	1	0	0	2	0	2	0	0	2	0
ON-OFF	Compact	AM1	Transfer input	1	100/110V AC	070	0	0	180									
				2	200/220V AC													
		AM2	a-contact input	1	100/110V AC	070	0	0	180									
				2	200/220V AC													
		AH1	Transfer input	1	100/110V AC	070	0	0	180									
	2			200/220V AC														
	DM2	a-contact input	0	24V DC	070	0	0	180										
			0	24V DC														
	DM0	Switching polarity	0	24V DC	070	0	0	180										
			0	24V DC														
	Economy	AE1	Transfer input	1	100/110V AC	120	0	0	360	0	360	700	02K	06K				
				2	200/220V AC													
				0	24V DC													
	AE2	a-contact input	1	100/110V AC	120	0	0	360	0	360	700	02K	06K					
			2	200/220V AC														
			0	24V DC														
	Standard	AD1	Transfer input	1	100/110V AC	300	0	0	300	700	700							
				2	200/220V AC													
		AD2	a-contact input	1	100/110V AC	300	0	0	300	700	700							
				2	200/220V AC													
0				24V DC														
7				115/120V AC														
AD0		Switching polarity	0	24V DC	300	0	0	300	700	700								
			0	24V DC														
HD1		Transfer input	1	100/110V AC	300	0	0	300	700	700	02K	06K						
			2	200/220V AC														
HD2	a-contact input	1	100/110V AC	300	0	0	300	700	700	02K	06K							
		2	200/220V AC															
HD0	Switching polarity	0	24V DC	300	0	0	300	700	700	02K	06K							
		0	24V DC															

  

Type	Category	①Actuator model		③Voltage	⑨Size(A)	015	020	025	032	040	050	065	080	100	125	150
					④Sizing	0	0	0	1	0	0	2	0	2	0	0
Emergency	Economy	ECR	a-contact input Power ON / OFF	1	100/110V AC	120	0	0	360	360						
				2	200/220V AC											
	Standard	ABR	a-contact input Power ON / OFF	1	100/110V AC	300	0	0	300	700	700					
				2	200/220V AC											
				0	24V DC											
		HBR	a-contact input Power ON / OFF	1	100/110V AC	300	0	0	300	700	700	02K	06K			
				2	200/220V AC											
0	24V DC															