

Product code □□□ DN □□ 1 T T T F - □□□ - □□

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

Code configuration (The contents are described in the specifications.)

①Actuator model / ②Valve model / ③Voltage / ④Sizing / ⑤Connection  
 ⑥Body material / ⑦Disk material / ⑧Seat material / ⑨ Size / ⑩ Option

Type	Category	①Actuator model		③Voltage	⑨Size(A)	080		100	125		150	200	250	300
					④Sizing	0	2	0	0	2	0	0	0	0
ON-OFF	Economy	AE1	Transfer input	1	100/110V AC	300	600		02K		06K			
				2	200/220V AC									
		AE2	a-contact input	1	100/110V AC	300	600		02K		06K			
				2	200/220V AC									
	Standard	AD1	Transfer input	1	100/110V AC	300	700							
				2	200/220V AC									
		AD2	a-contact input	1	100/110V AC	300	700							
				2	200/220V AC									
				0	24V DC									
				7	115/120V AC									
		AD0	Switching polarity	0	24V DC	300	700							
				0	24V DC									
		HD1	Transfer input	1	100/110V AC	300	700		02K		06K			
				2	200/220V AC									
		HD2	a-contact input	1	100/110V AC	300	700		02K		06K			
				2	200/220V AC									
0	24V DC													
HD0	Switching polarity	0	24V DC	300	700		02K		06K					
High performance	PHR	a-contact input Transfer input	1	100/110V AC	300	700		02K		06K				
			2	200/220V AC										
			3	24V AC										
			0	24V DC										
Proportional control	Economy	AEX	4 to 20mA, 1 to 5V Resistance input, etc.	1	100/110V DC	360	700		02K		06K			
	Standard	PDX	4 to 20mA, 1 to 5V Resistance input, etc.	2	200/220V AC									
				1	100/110V AC	300	700		02K		06K			
				2	200/220V AC									
				3	24V AC									
				0	24V DC									
				7	115/120V AC									
	8	230/240V AC												
	High performance	PHX	4 to 20mA 1 to 5V	1	100/110V AC	300	700		02K		06K			
				2	200/220V AC									
				3	24V AC									
				0	24V DC									
7				115/120V AC										
8				230/240V AC										
Type	Category	①Actuator model		③Voltage	⑨Size(A)	080		100	125		150	200	250	300
					④Sizing	0	2	0	0	2	0	0	0	0
Emergency	Standard	ABR	a-contact input Power ON / OFF	1	100/110V AC	300	700							
				2	200/220V AC									
				0	24V DC									
		HBR	a-contact input Power ON / OFF	1	100/110V AC	300	700		02K		06K			
				2	200/220V AC									
				0	24V DC									
	High performance	PBX	Proportional control 4 to 20mA, 1 to 5V Power ON / OFF	1	100/110V AC	300	700		02K		06K			
				2	200/220V AC									
				3	24V AC									
				0	24V DC									