

Product code	□ □ □ GS		□ □ 3 U U		□ - □ □ □ - □ □		Code configuration (The contents are described in the specifications.)																				
	①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩	①Actuator model / ②Valve model / ③Voltage / ④Sizing / ⑤Connection / ⑥Body material / ⑦Ball material / ⑧Seat material / ⑨Size / ⑩Option																
	Type	Category	①Actuator model		③Voltage		⑨Size(A)		015		020		025		032		040		050		065		080				
						④Sizing		0	2	0	2	0	2	0	2	0	2	0	2	0	2	1	0	2			
ON-OFF	Compact	AM1	Transfer input	1	100/110V AC	070	070	180	180																		
				2	200/220V AC																						
		AM2	a-contact input	1	100/110V AC	070	070	180	180																		
				2	200/220V AC																						
		AH1	Transfer input	1	100/110V AC	070	070	180	180																		
	2			200/220V AC																							
	DM2	a-contact input	0	24V DC	070	070	180	180																			
			0	24V DC																							
	DM0	Switching polarity	0	24V DC	070	070	180	180																			
			0	24V DC																							
	Economy	AE1	Transfer input	1	100/110V AC	120	120	360	120	360	120	360	700	360	700	02K		700	02K								
				2	200/220V AC																						
		AE2	a-contact input	1	100/110V AC	120	120	360	120	360	120	360	700	360	700	02K		700	02K								
				2	200/220V AC																						
	0			24V DC																							
	Standard	AD1	Transfer input	1	100/110V AC	300	300		300		300		300	700		700											
				2	200/220V AC																						
		AD2	a-contact input	1	100/110V AC	300	300	300	300	300	300	300	700		700												
				2	200/220V AC																						
				0	24V DC																						
7				115/120V AC																							
AD0		Switching polarity	0	24V DC	300	300	300	300	300	300	300	700		700													
			0	24V DC																							
HD1		Transfer input	1	100/110V AC	300	300	300	300	300	300	300	700		700	02K		700	02K									
			2	200/220V AC																							
HD2	a-contact input	1	100/110V AC	300	300	300	300	300	300	300	700		700	02K		700	02K										
		2	200/220V AC																								
		0	24V DC																								
HD0	Switching polarity	0	24V DC	300	300	300	300	300	300	300	700		700	02K		700	02K										
		0	24V DC																								
High performance	PHR	a-contact input Transfer input	1	100/110V AC	300	300	300	300	300	300	700		700	02K		700	02K										
			2	200/220V AC																							
			3	24V AC																							
			0	24V DC																							
Type	Category	①Actuator model		③Voltage		⑨Size(A)		015		020		025		032		040		050		065		080					
						④Sizing		0	2	0	2	0	2	0	2	0	2	0	2	0	2	1	0	2			
Proportional control	Compact	PAX	4 to 20mA 1 to 5V	1	100/110V AC	050	120		120																		
				2	200/220V AC																						
	Economy	AEX	4 to 20mA, 1 to 5V Resistance input, etc.	1	100/110V AC	120	120	360	120	360	120	360	700	360	700	02K		700	02K								
				2	200/220V AC																						
				6	100 to 240V AC																						
	Standard	PDX	4 to 20mA, 1 to 5V Resistance input, etc.	0	24V DC	120	120	300	120	300		300	700		700	02K		700	02K								
				1	100/110V AC																						
				2	200/220V AC																						
				3	24V AC																						
				0	24V DC																						
7				115/120V AC																							
8	230/240V AC																										
High performance	PHX	4 to 20mA 1 to 5V	1	100/110V AC	300	300	300	300	300	300	700		700	02K		700	02K										
			2	200/220V AC																							
			3	24V AC																							
			0	24V DC																							
			7	115/120V AC																							
8	230/240V AC																										
Emergency	Economy	ECR	a-contact input Power ON / OFF	1	100/110V AC	120	120	360	120	360	120	360		360													
				2	200/220V AC																						
	Standard	ABR	a-contact input Power ON / OFF	1	100/110V AC	300	300		300		300		300	700		700											
				2	200/220V AC																						
				0	24V DC																						
	High performance	HBR	a-contact input Power ON / OFF	1	100/110V AC	300	300	300	300	300	300	700		700	02K		700	02K									
				2	200/220V AC																						
				0	24V DC																						
				0	24V DC																						
	High performance	PBX	Proportional control 4 to 20mA, 1 to 5V Power ON / OFF	1	100/110V AC	300	300	300	300	300	300	700		700	02K		700	02K									
2				200/220V AC																							
3				24V AC																							
0				24V DC																							