

Type	Category	① Actuator model		③ Voltage	⑨ Size(A)	R040		R050		R065		R080		R100			R125		R150		
					④ Sizing	0	2	0	2	0	2	0	2	1	0	2	0	2	1	0	
ON-OFF	Compact	AM1	Transfer input	1	100/110V AC	180															
				2	200/220V AC																
		AM2	a-contact input	1	100/110V AC	180															
				2	200/220V AC																
		AH1	Transfer input	1	100/110V AC	180															
	2			200/220V AC																	
	DM2	a-contact input	0	24V DC	180																
			0	24V DC																	
	Economy	AE1	Transfer input	1	100/110V AC	120	360	700	360	700	02K		700	02K	06K	02K	06K				
				2	200/220V AC																
		AE2	a-contact input	1	100/110V AC	120	360	700	360	700	02K		700	02K	06K	02K	06K				
				0	24V DC																
	Standard	AD1	Transfer input	1	100/110V AC	300		300	700		700			700							
				2	200/220V AC																
		AD2	a-contact input	1	100/110V AC	300		300	700		700			700							
				2	200/220V AC																
				0	24V DC																
				7	115/120V AC																
		AD0	Switching polarity	0	24V DC	300		300	700		700			700							
				0	24V DC																
		HD1	Transfer input	1	100/110V AC	300		300	700		700	02K		700	02K	06K	02K	06K			
				2	200/220V AC																
	HD2	a-contact input	1	100/110V AC	300		300	700		700	02K		700	02K	06K	02K	06K				
			2	200/220V AC																	
HD0	Switching polarity	0	24V DC	300		300	700		700	02K		700	02K	06K	02K	06K					
		0	24V DC																		
High performance	PHR	a-contact input Transfer input	1	100/110V AC	300		300	700		700	02K		700	02K	06K	02K	06K				
			2	200/220V AC																	
			3	24V AC																	
			0	24V DC																	

Type	Category	① Actuator model		③ Voltage	⑨ Size(A)	R040		R050		R065		R080		R100			R125		R150	
					④ Sizing	0	2	0	2	0	2	0	2	1	0	2	0	2	1	0
Proportional control	Economy	AEX	4 to 20mA, 1 to 5V Resistance input, etc.	1	100/110V AC	120	360	700	360	700	02K		700	02K	06K	02K	06K			
				2	200/220V AC															
	PEX	4 to 20mA 1 to 5V	6	100 to 240V AC	300		300	700		700		700								
			0	24V DC																
	Standard	PDX	4 to 20mA, 1 to 5V Resistance input, etc.	1	100/110V AC	300		300	700		700	02K		700	02K	06K	02K	06K		
				2	200/220V AC															
				3	24V AC															
				0	24V DC															
				7	115/120V AC															
	High performance	PHX	4 to 20mA 1 to 5V	1	100/110V AC	300		300	700		700	02K		700	02K	06K	02K	06K		
				2	200/220V AC															
				3	24V AC															
				0	24V DC															
	Emergency	Economy	ECR	a-contact input Power ON / OFF	1	100/110V AC	120	360		360										
2					200/220V AC															
Standard		ABR	a-contact input Power ON / OFF	1	100/110V AC	300		300	700		700			700						
				2	200/220V AC															
				0	24V DC															
High performance		HBR	a-contact input Power ON / OFF	1	100/110V AC	300		300	700		700	02K		700	02K	06K	02K	06K		
				2	200/220V AC															
				0	24V DC															
High performance	PBX	Proportional control 4 to 20mA, 1 to 5V Power ON / OFF	1	100/110V AC	300		300	700		700	02K		700	02K	06K	02K	06K			
			2	200/220V AC																
			3	24V AC																
			0	24V DC																