

Product code	□□□	□R	□	□	1	T	T	P	-	□□□	-	□□	Code configuration (The contents are described in the specifications.)									
	①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩	①Actuator model / ②Valve model / ③Voltage / ④Sizing / ⑤Connection / ⑥Body material / ⑦Ball material / ⑧Seat material / ⑨Size / ⑩Option											
Type	Category	①Actuator model		③Voltage	⑨Size(A)	020	025		040	050		065	080		100							
						0	1	0	0	0	2	0	0	2	0							
ON-OFF	Economy	AE1	Transfer input	1	100/110V AC	120		120	360	700	700	0	0	2	0	02K						
				2	200/220V AC																	
		AE2	a-contact input	1	100/110V AC	120		120	360	700	700	0	0	0	2	0	02K					
				2	200/220V AC																	
					0	24V DC	120		120	360												
	Standard	AD1	Transfer input	1	100/110V AC	300		300	700	700	700	0	0	0	2	0	02K					
				2	200/220V AC																	
		AD2	a-contact input	1	100/110V AC	300		300	700	700	700	0	0	0	2	0	02K					
				2	200/220V AC																	
				0	24V DC																	
				7	115/120V AC																	
		8	230/240V AC																			
		AD0	Switching polarity	0	24V DC	300		300	700	700	700	0	0	0	2	0	02K					
	HD1	Transfer input	1	100/110V AC	300		300	700	700	700	0	0	0	2	0	02K						
			2	200/220V AC																		
	HD2	a-contact input	1	100/110V AC	300		300	700	700	700	0	0	0	2	0	02K						
2			200/220V AC																			
0			24V DC																			
HD0	Switching polarity	0	24V DC	300		300	700	700	700	0	0	0	2	0	02K							
High performance	PHR	a-contact input Transfer input	1	100/110V AC	300		300	700	700	700	0	0	0	2	0	02K						
			2	200/220V AC																		
			3	24V AC																		
			0	24V DC																		
Type	Category	①Actuator model		③Voltage	⑨Size(A)	020	025		040	050		065	080		100							
						0	1	0	0	0	2	0	0	2	0							
Proportional control	Economy	AEX	4 to 20mA, 1 to 5V Resistance input, etc.	1	100/110V AC	120		120	360	700	700	0	0	2	0	02K						
				2	200/220V AC																	
			PEX	4 to 20mA 1 to 5V	6	100 to 240V AC	120		300	700	700	0	0	0								
					0	24V DC																
	Standard	PDX	4 to 20mA, 1 to 5V Resistance input, etc.	1	100/110V AC	300		300	700	700	700	0	0	0	2	0	02K					
				2	200/220V AC																	
				3	24V AC																	
				0	24V DC																	
					7	115/120V AC																
					8	230/240V AC																
High performance	PHX	4 to 20mA 1 to 5V	1	100/110V AC	300		300	700	700	700	0	0	0	2	0	02K						
			2	200/220V AC																		
			3	24V AC																		
			0	24V DC																		
				7	115/120V AC																	
				8	230/240V AC																	
Emergency	Economy	ECR	a-contact input Power ON / OFF	1	100/110V AC	120		120	360	700	700	0	0	2	0	02K						
				2	200/220V AC																	
	Standard	ABR	a-contact input Power ON / OFF	1	100/110V AC	300		300	700	700	700	0	0	2	0	02K						
				2	200/220V AC																	
				0	24V DC																	
	High performance	HBR	a-contact input Power ON / OFF	1	100/110V AC	300		300	700	700	700	0	0	0	2	0	02K					
				2	200/220V AC																	
				0	24V DC																	
					1	100/110V AC	300		300	700	700	0	0	2	0	02K						
				2	200/220V AC																	
				3	24V AC																	
				0	24V DC																	