

Product code **MV** **5** **U** **U** **P** -

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

Code configuration (The contents are described in the specifications.)
 ①Actuator model / ②Valve model / ③Voltage / ④Sizing / ⑤Connection
 ⑥Body material / ⑦Ball material / ⑧Seat material / ⑨Size / ⑩Option

Type	Category	①Actuator model		③Voltage		⑨Size(A)		R010		R015		-015		-020	-025		-032	-040	-050			
						④Sizing		1	0	1	0	1	0	0	0	2	0	0	0	2		
Proportional control	Compact	PAX	4 to 20mA, 1 to 5V	1	100/110V AC	050	120	050	120	050	120											
				2	200/220V AC																	
	Economy	AEX	4 to 20mA, 1 to 5V Resistance input, etc.	1	100/110V AC		120		120		120		360				700					
				2	200/220V AC																	
	Standard	PEX	4 to 20mA, 1 to 5V	6	100 to 240V AC		120		120		120	300		300	700							
				0	24V DC																	
				1	100/110V AC		300		300	300			300	700								
				2	200/220V AC																	
				3	24V AC																	
				0	24V DC																	
	High performance	PDX	4 to 20mA, 1 to 5V Resistance input, etc.	7	115/120V AC		300		300		300			300	700							
				8	230/240V AC																	
				1	100/110V AC		300		300	300			300	700								
				2	200/220V AC																	
				3	24V AC																	
				0	24V DC																	
	High performance	PHX	4 to 20mA, 1 to 5V	7	115/120V AC		300		300		300			300	700							
				8	230/240V AC																	
1				100/110V AC		300		300	300			300	700									
2				200/220V AC																		
3				24V AC																		
0				24V DC																		
Emergency	High performance	PBX	Proportional control 4 to 20mA, 1 to 5V Power ON / OFF	1	100/110V AC		300		300		300			300	700							
				2	200/220V AC																	
				3	24V AC																	
				0	24V DC																	