

Product code □ □ □ Z- □ □ □ T □ □ □ - □ □ □ □ □ □ □

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

Code configuration (The contents are described in the specifications.)
 ① Actuator model / ② Valve model / ③ Voltage / ④ Sizing / ⑤ Connection
 ⑥ Body material / ⑦ Cap material / ⑧ Seat material / ⑨ Size / ⑩ Option

Type	Category	① Actuator model		③ Voltage		⑨ Size(A)		015		020		025		032		040	050		
						④ Sizing	0	2	0	2	0	2	0	2	0	0			
ON-OFF	Mini	CA1	Transfer input	1	100V AC		015		015										
				2	200V AC														
		PM1	a-contact input	1	100/110V AC		030		030		030		030						
				2	200/220V AC														
		CM1	Transfer input	1	100/110V AC		030		030		030		030						070
				2	200/220V AC														
		CM2	a-contact input	1	100/110V AC		030		030		030		030						070
				2	200/220V AC														
		CD2	a-contact input	0	24V DC		030		030		030		030						070
				4	12V DC														
	Compact	AM1	Transfer input	1	100/110V AC		030		030		030		030						070
				2	200/220V AC														
		AM2	a-contact input	1	100/110V AC		030		030		030		030						070
				2	200/220V AC														
		AH1	Transfer input	1	100/110V AC		030	070	030	070	030	070	030	070	030				070
	2			200/220V AC															
	DM2	a-contact input	0	24V DC		030	070	030	070	030	070	030	070	030				070	
			0	24V DC															
	Economy	AE1	Transfer input	1	100/110V AC		120		120		120		120						120
				2	200/220V AC														
AE2		a-contact input	1	100/110V AC		120		120		120		120						120	
			0	24V DC															
Proportional control	Mini	CMX	4 to 20mA	1	100/110V AC		030		030		030		030					070	
				2	200/220V AC														
				0	24V DC														
	Compact	PAX	4 to 20mA 1 to 5V	1	100/110V AC		050		050		050		050					120	
				2	200/220V AC														
	Economy	AEX	4 to 20mA, 1 to 5V Resistance input, etc.	1	100/110V AC		120		120		120		120					120	
2				200/220V AC															
PEX	4 to 20mA 1 to 5V	6	100 to 240V AC		120		120		120		120					120			
		0	24V DC																
Type	Category	① Actuator model		③ Voltage		⑨ Size(A)		015		020		025		032		040	050		
						④ Sizing	0	2	0	2	0	2	0	2	0	0	0		
Emergency	Compact	ACR	Power ON / OFF	2	100 to 220V AC		030		030		030		030						
	Economy	ECR	a-contact input Power ON / OFF	1	100/110V AC		120		120		120		120				120		
2				200/220V AC															