



MA-WTG-2TG0-350
MA-WTG-2TG0-400

呼び径	d	L	D	C	n-h	H2	質量[kg]	Cv値	操作機型式	減速比
40 A	40	40	80	95	4-15	206	6.3	85	MAG-F07	24:1
50 A	50	40	90	105	4-15	211	6.4	145	MAG-F07	24:1
65 A	65	40	115	130	4-15	223	6.8	290	MAG-F07	24:1
80 A	80	50	126	145	4-19	255	7.8	450	MAG-F07	24:1
100 A	105	50	146	165	8-19	266	8.1	780	MAG-F07	24:1
125 A	130	50	181	200	8-19	283	8.8	1200	MAG-F07	24:1
150 A	154	50	211	230	8-19	298	11	1800	MAG-F07	24:1
200 A	204	50	257	280	8-23	321	12	3200	MAG-F07	24:1
250 A	253	50	322	345	12-23	343	15	5100	MAG-F07	24:1
300 A	300	55	367	390	12-23	369	19	7200	MAG-F07	24:1
350 A	340	70	410	435	12-25	398	27	8900	MAG-F07	24:1
400 A	387	70	470	495	16-25	422	31	11000	MAG-F07	24:1

NOTE
(a) ギアのハンドルは取り外した状態で出荷

No	DESCRIPTION	MATERIALS	REQ'D	REMARKS
8	ギア	FC250(ケース)	1	(a)
7	ブラケット	SUS304/SCS13A	1	
6	コネクタ	SUS304	1	
5	コネクタ	SUS304/SCS13A	1	
4	グランドパッキン	膨張黒鉛	1	
3	ステム	SUS420J2	1	
2	弁体	SUS420J2/J1	1	
1	本体	SCS13A	1	

MARK	DATE	BY	DATE	SCALE	NON	DWG No.	WT-2TG0-G-MA5
REVISIONS							
MV-2916							

APPR'D H. F
CHK'D K. Y
DESIGN
DRAWN S. O
TITLE J5K ウェハ形
WT型手動バタフライダンパ
MODEL MA-WTG-2TG0