



呼び径	d	L	D	C	n-h	H	質量(kg)	Cv値	操作機型式	ランク
40 A	40	40	80	95	4-15	384	11	85	PBX-300	0
50 A	50	40	90	105	4-15	389	11	145	PBX-300	0
65 A	65	40	115	130	4-15	401	12	290	PBX-300	0
80 A	80	50	126	145	4-19	433	13	450	PBX-300	0
100 A	105	50	146	165	8-19	444	13	780	PBX-300	0
125 A	130	50	181	200	8-19	461	14	1200	PBX-300	0
150 A	154	50	211	230	8-19	476	15	1800	PBX-300	0
200 A	204	50	257	280	8-23	499	17	3200	PBX-300	0
250 A	253	50	322	345	12-23	521	20	5100	PBX-300	0
							20		PBX-700	2
300 A	300	55	367	390	12-23	547	24	7200	PBX-300	0
							24		PBX-700	2
350 A	340	70	410	435	12-25	598	32	8900	PBX-700	0
							620		33	PBX-02K
400 A	387	70	470	495	16-25	622	36	11000	PBX-700	0
							644		38	PBX-02K

NOTE
 付属品
 ・ケーブルコネクタ(ナイロン製), G1/2, 適合ケーブルφ6~12
 ・プラグ

7	電動操作機	AC4C	1	
6	コネクタ	SCS13A	1	
5	ブラケット	SUS304	1	
4	グランドパッキン	膨張黒鉛	1	
3	ステム	SUS420J2	1	
2	弁体	SUS420J2/J1	1	
1	本体	SCS13A	1	
No	DESCRIPTION	MATERIALS	REQ'D	REMARKS

			APPR'D	H.F	TITLE	J 5 K ウエハー式 WT 型電動緊急遮断型コントロールダンパ					
			CHK'D	K.Y		MODEL	PBXWT**2TGO				
			DESIGN		MARK		DATE	BY	SCALE	NON	DWG No.
			DRAWN	S.O							
			DATE	'18-03-01							
REVISIONS											
MV-2691											